



# HP Recycled<sup>1</sup> Removable Adhesive Fabric, 3-in Core



**The HP large format printing system—the complete solution**

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



**Print high-quality, repositionable graphics that stick to non-porous surfaces**

**Easy-to-install, reposition, and remove**

Enjoy the ease of working with this repositionable adhesive-back fabric that is easy to install, reposition, and remove with virtually no residue. The special adhesive is designed to stick to non-porous surfaces to create seamless, photographic image quality wall and floor graphics.

**Made with recycled water bottles<sup>2</sup> and coating materials**

HP Recycled<sup>1</sup> Removable Adhesive Fabric is made with recycled water bottles<sup>2</sup> and coating materials. Recycling beverage containers (and other materials) saves energy, reduces greenhouse gas emissions, and diverts material from landfills.<sup>3</sup>

**Grab attention with vibrant image quality for a variety of applications**

Capture realistic graphic detail for applications from wall murals and event signage to retail displays. Achieve a high-quality look with this versatile, easy-to-handle, repositionable self-adhesive fabric—ideal for a wide range of indoor and outdoor applications.

Target customers	Applications	Benefits
Print service providers	Wall murals	Designed for easy installation, repositioning, and removal for a wide range of applications
Government agencies	Wall cut-outs	Ability to contour cut and apply without stretching
Graphic artists	Indoor and short-term outdoor signage	Smooth, matte finish for deep blacks, vivid colors, and high ink saturation
Sign shops	Point-of-purchase displays	Outstanding photographic image quality
Retail	Trade show graphics	B1, ASTM E84 flame resistance <sup>4</sup>
	Decals	Compatible with Original HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide XL pigment inks, and HP Latex Inks
	Window graphics	Slip resistant <sup>5</sup> for floor graphics <sup>6</sup>
	Floor graphics	



## Technical specifications

<b>Ink compatibility</b>	Compatible with HP Bright Office Inks, HP Vivid Photo Inks, HP PageWide XL pigment inks, and HP Latex Inks			
<b>Weight (With liner)</b>	289 g/m <sup>2</sup> per ISO 536 Test Method			
<b>Thickness (With liner)</b>	304 microns/12 mil per ISO 20534 Test Method			
<b>Liner</b>	120 g/m <sup>2</sup> , double-sided PE-coated silicone paper			
<b>Adhesive</b>	Clear, removable, and repositionable adhesive			
<b>Removability</b>	Up to 3 years removable/repositionable indoors			
<b>Opacity</b>	>85% per TAPPI T-425 Test Method and ISO 2471 Test Method			
<b>Brightness</b>	>97 per TAPPI T-452 Test Method			
<b>Whiteness</b>	118 per ASTM E313-98 Test Method			
<b>Finish</b>	Matte			
<b>Slip rating</b>	In compliance according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586) <sup>5</sup>			
<b>Operating temperature</b>	15 to 25° C / 59 to 77° F			
<b>Operating humidity</b>	20 to 80% RH			
<b>Water resistance</b>	Moderately water-resistant <sup>7</sup>			
<b>Wind orientation</b>	Print side out			
<b>Core size</b>	3-in core with a removable 2-in core adapter			
<b>Dry time</b>	Immediate			
<b>Flame resistance</b>	B1, and ASTM E84 approved fire certifications <sup>4</sup>			
<b>Lamination</b>	For additional protection, liquid or spray coatings are recommended <sup>8</sup>			
<b>HP PageWide XL cutter</b>	The weight of this material is higher than the recommended weight limit for the HP PageWide XL cutter, which may reduce the expected life of the cutter			
<b>Shelf life</b>	1 year, unopened in original packaging			
<b>Storage temperature</b>	10 to 27° C / 50 to 80° F			
<b>Storage humidity</b>	35 to 65% RH			
<b>Environmental</b>	Adhesive fabric made with recycled water bottles <sup>2</sup> and coating materials, REACH compliant <sup>9</sup>			
<b>Finishing/post processing</b>	Use a carbide knife for kiss and die cutting			
<b>Installation tip</b>	To install the graphic, peel 101 millimeters (4 inches) of the release liner off the graphic and place on wall or surface. Continue to peel back 101 millimeters (4 inches) of the liner incrementally while mounting.			
<b>Country of origin</b>	Product of China			
<b>Ordering information</b>	<b>Product numbers</b>	<b>Roll sizes</b>	<b>UPC</b>	<b>Region</b>
	5L2S6A	610 mm x 30,5 m (24 in x 100 ft)	848412026474	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2S7A	914 mm x 30,5 m (36 in x 100 ft)	848412026481	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2S8A	1067 mm x 30,5 m (42 in x 100 ft)	848412026498	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2S9A	1372 mm x 30,5 m (54 in x 100 ft)	848412026504	United States, Canada, Latin America, Europe, Middle East, and Africa
	5L2T0A	1524 mm x 30,5 m (60 in x 100 ft)	848412026511	United States, Canada, Latin America, Europe, Middle East, and Africa
<b>Warranty</b>	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <a href="https://HPLFMedia.com/hp/MediaWarranties">HPLFMedia.com/hp/MediaWarranties</a> . To obtain warranty service, please contact Brand Management Group customer support at <a href="https://HPLFMedia.com/hp/en/contactus">HPLFMedia.com/hp/en/contactus</a> .			

<sup>1</sup> Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.

<sup>2</sup> 100% of total PET resin in the product made from recycled water bottles. The coating does not contain recycled materials. Compliant with Global Recycled Standard (GRS) Version 4.0.

<sup>3</sup> According to "The Ecology of Recycling," published on United Nations website, UN Chronicle; see [un.org/en/chronicle/article/ecology-recycling](https://un.org/en/chronicle/article/ecology-recycling) and "Reducing and Reusing Basics," US EPA, March 2022, see <https://www.epa.gov/recycle/reducing-and-reusing-basics>.

<sup>4</sup> B1, ASTM E84 approved fire certifications.

<sup>5</sup> Slip resistance for dry environments based on testing by Sotter Engineering Corporation, February 2022, in compliance according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586).

<sup>6</sup> Recommended on indoor smooth, non-porous, sealed flat and dry surfaces for up to 3 months. Slip resistance for dry environments based on testing by Sotter Engineering Corporation, February 2022, in compliance according to ANSI A137.1/A326.3 and AS HB198:2014 (AS/NZS 4586).

<sup>7</sup> Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see [HPLFMedia.com/hp/print/permanence](https://HPLFMedia.com/hp/print/permanence).

<sup>8</sup> For additional protection, we recommend Marabu ClearShield Professional Wall Armor

<sup>9</sup> See the HP REACH Declaration published at [HP.Printing.Products.and.Consumable.Supplies](https://HPLFMedia.com/hp/en/contactus).

For detailed information on the HP large format printing materials portfolio and to order, see [HPLFMedia.com](https://HPLFMedia.com)

© 2025 HP Development Company, L.P. © 2025 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group under license from HP Development Company, L.P.

